

Page: 1 of 6

This version issued: May, 2017

Phone: +61 3 8080 1420 (any time)

Section 1 - Identification of The Material and Supplier

Dingo Cement Pty Ltd

Unit 8 27-35 Huntingdale Rd

Burwood 3125 Victoria Australia

Chemical nature: Blend of Portland cement and other ingredients.

Trade Name: Bastion High Strength Concrete

Note that this SDS is intended for Bastion branded products.

Product Use: Bastion High Strength Concrete Mix is suitable for Larger sized Posts, Fence Corner

Posts, Gate Posts and wherever high strength concrete is required 55 mpa.

Creation Date: January, 2017

This version issued: May, 2017 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. Xi, Irritating. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG)

Code, IATA or IMDG/IMSBC criteria. **UN Number:** None allocated



GHS Signal word: WARNING

Skin Irritation Category 2

Skin Sensitisation Category 1

Serious eye irritation Category 2/2A

Specific Target Organ Toxicity - Single Exposure Category 3

Specific Target Organ toxicity - repeated exposure Category 2

Hazardous to aquatic environment Short term/Acute Category 3

HAZARD STATEMENT:

AUH066: Repeated exposure may cause skin dryness or cracking.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

H402: Harmful to aquatic life due to high pH.

PREVENTION

P102: Keep out of reach of children.

P260: Do not breathe dusts.

P262: Do not get in eyes, on skin, or on clothing.

P271: Use only outdoors or in a well ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P314: Get medical advice or attention if you feel unwell.

P353: Rinse skin or shower with water.

SAFETY DATA SHEET

Issued by: Dingo Cement Pty Ltd Phone: +61 3 8080 1420 (any time)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Page: 2 of 6

This version issued: May, 2017

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P370+P378: Not combustible. Use extinguishing media suited to burning materials.

STORAGE

P403: Store in a well-ventilated place.

P405: Store locked up.

P402+P404: Store in a dry place. Store in a closed container.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Grey coloured powder.

Odour: No odour.

Major Health Hazards: irritating to eyes, respiratory system and skin, possible skin sensitiser, repeated exposure

may cause skin dryness or cracking.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m³)
Portland cement	65997-15-1	10-30	10	not set
Silica (Crystalline)	14808-60-7	30-70	0.1	not set
Aggregate	not set	30-70	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Quickly and gently brush away excess particles. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Quickly and gently brush particles from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

SAFETY DATA SHEET



Page: 3 of 6

This version issued: May, 2017

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

No fire decomposition products are expected from this product at temperatures normally achieved in a fire.

Extinguishing Media: Not combustible. Use extinguishing media suited to burning materials. **Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: Does not burn.
Upper Flammability Limit: Does not burn.
Lower Flammability Limit: Does not burn.

Autoignition temperature: Not applicable - does not burn.

Flammability Class: Does not burn.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include no specific manufacturer recommendations. Use impermeable gloves with care. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that dusts are likely to build up in cleanup area, we recommend that you use a suitable dust mask.

Stop leak if safe to do so, and contain spill. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Consider vacuuming if appropriate. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure LimitsTWA (mg/m³)STEL (mg/m³)Portland cement10not setSilica (Crystalline)0.1not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. **Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a

fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: There is no specific recommendation for any particular protective material type.

SAFETY DATA SHEET



Page: 4 of 6 This version issued: May, 2017

Respirator: If there is a significant chance that dusts are likely to build up in the area where this product is being used, we recommend that you use a suitable dust mask.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Grey coloured powder.

Odour:

Boiling Point:

Freezing/Melting Point:

Volatiles:

No odour.

Not available.
>1200°C

No data.

Vapour Pressure: Nil at normal ambient temperatures.

Vapour Density: Not applicable. Specific Gravity: No data.

Water Solubility: Forms slurry which sets or hardens on standing.

pH: About 12

Volatility: Nil at normal ambient temperatures.

Odour Threshold:

Evaporation Rate:

Coeff Oil/water Distribution:

Viscosity:

No data

Not applicable.

Not applicable.

Autoignition temp: Not applicable - does not burn.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: Keep containers tightly closed. Containers should be kept dry.

Incompatibilities: water, acids, zinc, tin, aluminium and their alloys.

Fire Decomposition: No significant quantities of decomposition products are expected at temperatures normally achieved in a fire. Silicon compounds.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient Risk Phrases

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations. Depending on the type of handling and use (e.g. grinding, drying, mix, load, unload), airborne respirable crystalline silica (quartz - cristobalite) may be generated. Prolonged and/or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness. Occupational exposure to respirable crystalline silica dust should be monitored and controlled. This product should be handled with care to avoid dust generation.

Potential Health Effects

Inhalation:

Short Term Exposure: This product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased if treatment is prompt.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

SAFETY DATA SHEET

Issued by: Dingo Cement Pty Ltd Phone: +61 3 8080 1420 (any time)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)



Page: 5 of 6

This version issued: May, 2017

Long Term Exposure: Repeated exposure may cause skin dryness or cracking.

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

This product is unlikely to adversely effect the environment. Salts, acids and bases are typically diluted and neutralised when released to the environment in small quantities. However, until diluted or neutralised it will kill any aquatic organisms it contacts due to high pH.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle product and containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site.

Section 14 - Transport Information

UN Number: This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS
SWA
Australian Inventory of Chemical Substances
Safe Work Australia, formerly ASCC and NOHSC
CAS number
Chemical Abstracts Service Registry Number
International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

SAFETY DATA SHEET

Issued by: Dingo Cement Pty Ltd Phone: +61 3 8080 1420 (any time)



Page: 6 of 6 This version issued: May, 2017

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

Copyright © Kilford & Kilford Pty Ltd, May, 2017.

http://www.kilford.com.au/ Phone (02)9251 4532

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)